

IN THE CLAIMS:

Please amend the claims as follows:

- Sub
E1
- DI
1. (currently amended) An apparatus comprising:
a data processing device; ~~comprising a first group of control elements~~
~~and a second group of control elements; and~~
a first group of control elements and a second group of control elements
integrated directly on said data processing device; and
a display comprising a display area for rendering images generated by
said data processing device, said display coupled to said data processing device
at a pivot point and rotatable around said pivot point from a first position to a
second position, wherein said display is viewable in both said first position and
said second position and wherein both said first and second groups of control
elements are exposed when said display is in said second position, and wherein
only said second group of control elements are exposed when said display is in
said first position, and
wherein said first and second groups of control elements are positioned
outside of said display area.

2. (previously presented) The apparatus as in claim 1 wherein said first
group of control elements are covered by said display when said display is in
said first position.

09/714,320

2

04676.P004X

3. (previously presented) The apparatus as in claim 1 wherein said first group of control elements comprise a keyboard.

4. (previously presented) The apparatus as in claim 2 wherein said second group of control elements are not covered by said display when said display is in said first position.

5. (original) The apparatus as in claim 4 wherein said second group of control elements comprise a control knob and a set of control buttons.

6. (previously presented) The apparatus as in claim 1 wherein said display is inverted when in said second position relative to said first position.

7. (previously presented) The apparatus as in claim 6 further comprising: a switch configured to trigger when said display is rotated from said second position to said first position.

8. (original) The apparatus as in claim 7 further comprising: image inversion logic to invert images on said display responsive to said switch triggering.

Claims 9-15 (canceled)

09/714,320

3

04676.P004X

16. (currently amended) An apparatus comprising:
a data processing device;
a display having a display area defining a plane, the display rotatably
coupled to said data processing device and configured to pivot around a pivot
point within ~~[[a]]~~ said plane from a first position to a second position, wherein
images displayed on said display are viewable in both said first position and said
second position.

Don't

17. (previously presented) The apparatus as in claim 16 wherein both a
first group of control elements and a second group of control elements are
exposed when said display is in said second position, and wherein only said
second group of control elements are exposed when said display is in said first
position.

18. (previously presented) The apparatus as in claim 17 wherein said first
group of control elements comprises a keyboard.

19. (previously presented) The apparatus as in claim 18 wherein said
second group of control elements comprise a control knob and a set of control
buttons.

20. (original) The apparatus as in claim 16 further comprising:
a switch configured to trigger when said display is rotated from said first
position to said second position.

09/714,320

4

04676.P004X

21. (original) The apparatus as in claim 20 further comprising:
image inversion logic to invert images on said display responsive to said
switch triggering.

22. (original) The apparatus as in claim 19 wherein said control knob is
configured to scroll between items within a list.

23. (original) The apparatus as in claim 22 wherein one of said control
buttons is configured to select items within said list.

24. (original) The apparatus as in claim 23 wherein one of said control
buttons is configured to back out of selected items.

25. (original) The apparatus as in claim 19 wherein said control buttons
and control knob are user-programmable.

26. (currently amended) An apparatus comprising:
a data processing device; ~~comprising a first group of control elements and~~
~~a second group of control elements; and~~
a first group of control elements and a second group of control elements
integrated directly on said data processing device; and

a display having a viewable area for viewing images generated by said
data processing device, said display cooperatively engaged with said data

processing device to move from a first position to a second position, wherein images are viewable within said viewable area when said display is in said first position and said second position, and

wherein both said first group of control elements and said second group of control elements are exposed when said display is in said second position, and wherein only said second group of control elements are exposed when said display is in said first position, both said first and second groups of control elements positioned outside of said viewable area of said display.

27. (previously presented) The apparatus as in claim 26 wherein said display is rotatably coupled to said data processing device and configured to rotate within a plane substantially perpendicular to said display's axis of rotation between said first position and said second position.

2928. (currently amended) The apparatus as in claim 26 wherein said first group of control elements comprises a keyboard.

3029. (currently amended) The apparatus as in claim 298 wherein said second group of control elements comprises a control knob.

3130. (currently amended) The apparatus as in claim 26 wherein said second position is inverted with respect to said first position.

Donel.

~~32131.~~ (currently amended) The apparatus as in claim ~~340~~ wherein images displayed on said display are inverted relative to said display when said display is moved between said first position and said second position.

~~3332.~~ (currently amended) The apparatus as in claim ~~321~~ further comprising a switch configured to trigger when said display is rotated from said first position to said second position and image inversion logic to invert images on said display responsive to said switch triggering.
